MAXXON®
COMMERCIAL
Skim Fill™



THE PERFECT ALL-PURPOSE PATCH FOR IMPERFECT SUBFLOORS.

Maxxon® Commercial Skim Fill™ is an easy to mix, fast-setting, polymer-modified cement patch for correcting interior subfloor imperfections. Its high compressive strength and exceptional bonding properties deliver a smooth, strong surface that's ready for floor covering in as little as 30 minutes.

- Polymer-modified cement-based patch
- Exceptional bond and compressive strength (4,000 psi+)
- Can be installed over wet slabs (up to 100% RH)
- Featheredge up to 1/2", no depth limitation in confined spaces
- Fast setting — install flooring in as little as 30 minutes
- Self-drying

BENEATH IT ALL, MAXXON DELIVERS.

WHERE TO USE

Application

Smoothing and repairing

Subfloor

Ideal for concrete and wood

TYPICAL RANGE:
4,000+
PSI

MAXXON®
COMMERCIAL
Skim Fill™

VERSATILITY AND STRENGTH FROM FEATHEREDGE TO DEEP FILLS.

Tackle every level of subfloor imperfection with Maxxon® Commercial Skim Fill™. The easy-to-trowel formula can be installed from a true featheredge up to 1/2" (12 mm) and it has no depth limitation in confined spaces.

Whether you need a skim coat or deeper fill to prep an old subfloor or green concrete, Skim Fill delivers the versatility and strength required to get the job done right.

PRODUCT INFORMATION

Compressive Strength (Modified ASTM C109)	4,000 psi (24.6 MPa)
Pot Life	15–20 minutes
Flooring Install	30–60 minutes
Coverage (Per 20 lb. bag)	Skim coat: 400–600 ft² (37.2–55.7 m²) 1/8" (3 mm): 60–72 ft² (5.6–6.6 m²) 1/4" (6 mm): 30–36 ft² (2.8–3.3 m²) 1/2" (12 mm): 15–18 ft² (1.4–1.7 m²)
Installation Temperature	Above 50 °F (10 °C) for at least 24 hours prior to installation
RH Limits	Can be installed over green concrete up to 100% RH



INSTALLATION & LIMITATIONS

See technical data sheet available at Maxxon.com for limitations and complete installation instructions.

PACKAGING

20 lbs (9.07 kg)

PRO TIP

Reducing the mixing water by as little as 5 – 10% can help hold the slope making deep fill applications easier.

Maxxon Corporation
920 Hamel Road PO Box 253
Hamel, Minnesota 55340
800-356-7887
maxxon.com
info@maxxon.com

@Maxxon.Corporation
maxxon-corporation

©2024 Maxxon Corporation. All Rights Reserved. Maxxon Commercial Pro Level-Right and associated logos are registered trademarks of Maxxon Corporation, Hamel, MN, USA. SS010-04/25