MAXXON®
COMMERCIAL PRO
Level-Right®

Products for approved Maxxon applicators



THE ROCK-SOLID SOLUTION FOR UNEVEN FLOORS.

Maxxon® Commercial Pro Level-Right® is a self-leveling, hydraulic cement-based underlayment designed to flatten and smooth concrete slabs.

- High compressive strengths—ideal for commercial, retail and institutional projects
- Suitable for small repair jobs to large projects
- No special subfloor prep, old floor removal or hand finishing required
- Cost-effective solution installed by approved applicators
- Batch mixed on site to meet project needs
- Cap existing floor goods and adhesive residue
- GREENGUARD Gold Certified

BENEATH IT ALL, MAXXON DELIVERS.™

WHERE TO USE

Application
Commercial renovation and concrete construction.

Subfloor
Interior wood, concrete, terrazzo, ceramic, quarry, marble tile, old vinyl tile and radiant heat floors.

TYPICAL RANGE:
5,000-7,000
PSI

MAXXON®
COMMERCIAL PRO
Level-Right®

Products for approved Maxxon applicators

SELF-LEVELING. FAST INSTALL.

Maxxon Commercial Pro Level-Right is the affordable, time-saving choice for resurfacing concrete slabs. Self-leveling to ¼ inch, the robust formulation can be applied from featheredge to 3 inch depths to correct uneven subfloors, yielding a smooth, level surface suitable for virtually any floor covering.

Batch mixed on site, it installs fast — covering up to 40,000 square feet per day — and can be walked on 2 to 4 hours after set. Ceramic tile can be installed within 2 to 4 hours after set and other floor goods can be installed after a successful moisture test.

PRODUCT INFORMATION

Compressive Strength (Modified ASTM C109)	Typical range of 5,000–7,000 psi (34.5–48.3 MPa)
Installation Depths	From featheredge to 3 in. (0–76 mm) For deeper pours, contact Maxxon
Dry Density	115–125 lbs/ft^3 (1842–2002 kg/m^3)
Fire Performance (ASTM E84)	Flame spread: 0 Fuel contribution: 0 Smoke development: 0



INSTALLATION & LIMITATIONS

See technical data sheet available at Maxxon.com for limitations and complete installation instructions.

PACKAGING

80 lbs (36 kg)

FIRE RATINGS

Underwriters Laboratory International UL ER #8477-01. See technical data sheet for complete UL and fire assembly information.

LEED INFORMATION

For information regarding how Maxxon Commercial Pro Level-Right may earn points toward LEED project certification, contact us at 800-356-7887 or visit www.maxxon.com/go_green.

PRO TIP

May be used as part of a wear surface system — contact Maxxon for details.

GREENGUARD GOLD
GREENGUARD
UL LISTED

Maxxon Corporation
920 Hamel Road PO Box 253
Hamel, Minnesota 55340
800-356-7887
maxxon.com
info@maxxon.com

@Maxxon.Corporation
maxxon-corporation

©2025 Maxxon Corporation. All Rights Reserved. Maxxon Commercial Pro Level-Right and associated logos are registered trademarks of Maxxon Corporation, Hamel, MN, USA. CP-002