

MAXXON®
COMMERCIAL

**Multi-Purpose
PSA**

ADHESIVE



EASY INSTALLATION. ADJUSTABLE PLACEMENT.

Maxxon® Commercial Multi-Purpose PSA is a versatile pressure-sensitive adhesive engineered for a broad range of resilient and modular floor coverings. It delivers exceptional initial tack and reliable bond performance while remaining permanently tacky after drying, supporting long-term performance while simplifying future floor covering replacement.

- Versatile installation using semi-wet or dry-set methods
- Fast grab adhesion
- Installation flexibility for easy adjustments
- Permanently tacky after drying for resilient flooring
- High moisture and pH resistance

WHERE TO USE

Suitable for installation of:

- Luxury Vinyl Tile (LVT)
- Luxury Vinyl Plank (LVP)
- Vinyl Composition Tile (VCT)
- Vinyl Sheet Flooring and Other Sheet Goods (limited to 90% RH and pH 10)
- Modular Carpet Tile
- Other approved resilient flooring materials

BENEATH IT ALL, MAXXON DELIVERS.™

Multi-Purpose PSA

ADHESIVE

BUILT TO BOND. DESIGNED TO PERFORM.

Maxxon® Commercial Multi-Purpose PSA delivers true pressure-sensitive performance for efficient flooring installation. Designed to remain permanently tacky after drying, it provides a strong initial grab while allowing flooring to be repositioned during installation for precise alignment. For select floor coverings, its permanently tacky bond can also simplify future flooring replacement when needed. Its exceptional tack accelerates installation, and the shear bond strength provides reliable performance.

PRODUCT INFORMATION

Coverage	1/16" x 1/32" x 1/32" U Notch	Up to 260 ft²/gal
	1/16" x 1/16" x 1/16" Square Notch	Up to 180 ft²/gal
	3/8" Short Nap Paint Roller	Up to 360 ft²/gal
Polymer Type	Acrylic	
Shelf Life	2 Years (unopened)	
Time to Traffic	Foot Traffic - dry-set: immediate Foot Traffic - semi-wet: 12 Hours Heavy Traffic: 24 Hours Floor cleaning or finishing: 48 Hours Heat welding: 6 Hours	
ASTM F2170	RH 99% provided the site is absent of hydrostatic pressure	
ASTM F710	pH 7-12 with limitations	



INSTALLATION & LIMITATIONS

See technical data sheet available at maxxon.com for limitations and complete installation instructions.

PACKAGING

4 gal. (15.14 L) bucket

PRO TIP

The adhesive is ready for floor covering when the valleys are clear and while the ridges remain white.

For dry application: The adhesive is ready for floor covering when the adhesive is clear and tacky.

Maxxon Corporation
920 Hamel Road, PO Box 253
Hamel, Minnesota 55340
800-238-8461
maxxon.com
info@maxxon.com

@maxxon.corporation
 maxxon-corporation