

MAXXON®
COMMERCIAL

**Transitional
PSA**

ADHESIVE



VERSATILE INSTALLATION. FAST GRAB. EXCEPTIONAL BOND.

Maxxon® Transitional PSA is approved for dry-set and semi-wet installations. It offers the easy handling of a pressure-sensitive adhesive while developing into a superior, firm-set bond. Aggressive early tack and faster bond help lock flooring in place quickly, minimizing movement. Its rapid flash time reduces wait time to help keep installations moving.

- Versatile installation using semi-wet or dry-set methods
- Exceptional shear strength for high-traffic areas and rolling loads
- Provides fast, early grab of the floor covering while developing a superior, firm-set bond
- Up to 99% RH tolerance
- High moisture and pH resistance

WHERE TO USE

Suitable for installation of:

- Luxury Vinyl Tile (LVT)
- Luxury Vinyl Plank (LVP)
- Vinyl Composition Tile (VCT)
- Vinyl Sheet Flooring and Other Sheet Goods (limited to 90% RH and pH 10)
- Modular Carpet Tile
- Other approved resilient flooring materials

BENEATH IT ALL, MAXXON DELIVERS.™

**PSA CONVENIENCE.
FIRM-SET CONFIDENCE.**

For installations where fast grab and a stronger bond are the priority, Maxxon® Commercial Transitional PSA is designed to perform across a wide range of resilient flooring applications. Its high shear strength helps withstand heavy traffic and rolling loads, while broad substrate compatibility and moisture tolerance up to 99% RH provide confidence on challenging commercial projects. Transitional PSA helps contractors maximize productivity without sacrificing long-term performance.

PRODUCT INFORMATION

Coverage	1/16" x 1/32" x 1/32" U Notch	Up to 260 ft²/gal
	1/16" x 1/16" x 1/16" Square Notch	Up to 180 ft²/gal
	3/8" Short Nap Paint Roller	Up to 360 ft²/gal
Polymer Type	Acrylic	
Shelf Life	2 Years (unopened)	
Time to Traffic	Foot Traffic - dry-set: immediate Foot Traffic - semi-wet: 12 Hours Heavy Traffic: 24 Hours Floor cleaning or finishing: 48 Hours Heat welding: 6 Hours	
ASTM F2170	RH 99% provided the site is absent of hydrostatic pressure	
ASTM F710	pH 7-12 with limitations	

INSTALLATION & LIMITATIONS

See technical data sheet available at maxxon.com for limitations and complete installation instructions.

PACKAGING

4 gal. (15.14 L) bucket

PRO TIP

The adhesive is ready for floor covering when the valleys are clear and while the ridges remain white.

For dry application: The adhesive is ready for floor covering when the adhesive is clear and tacky.



Maxxon Corporation
920 Hamel Road, PO Box 253
Hamel, Minnesota 55340
800-238-8461

maxxon.com
info@maxxon.com

[@maxxon.corporation](https://www.facebook.com/maxxon.corporation)
[maxxon-corporation](https://www.linkedin.com/company/maxxon-corporation)