

**MAXXON®**

**VenTek™  
Rainscreen**



**REDUCE MOISTURE  
INTRUSION.  
PREVENT MOISTURE  
DAMAGE.**

VenTek™ Rainscreen shields buildings from moisture intrusion by creating a drainage plane with ventilation in the exterior wall system. Composed of a breathable spunbond fabric, VenTek Rainscreen allows moisture to drain down and out while promoting air flow to inhibit mold growth, rot, and other moisture-related damage.

- Printed gridlines to make installation faster and easier
- Entangled mesh with breathable backer fabric
- Double protection: excellent ventilation and drainage
- Creates resilient drainage plane
- Superior fabric to reduce moisture contact with building

**WHERE TO USE**

*Application*

Exterior Cladding

*For use under all absorptive sidings including: Stone, Stucco, Brick, Fiber cement board, Wood siding*

# MAXXON®

## VenTek™ Rainscreen

### DRAINAGE AND VENTILATION TO PROTECT BUILDINGS.

Buildings damaged by moisture can lead to extensive, costly repairs and potential health risks for occupants. With a VenTek Rainscreen you can mitigate moisture-related problems by cost-effectively upgrading the building envelope to support excellent air flow and moisture evaporation.

As climate change intensifies the frequency and intensity of precipitation, VenTek Rainscreen offers an economical and simple way to protect the durability and integrity of buildings. With its superior fabric with printed gridlines, VenTek Rainscreen will provide superior protection with fast and easy installation.

### PRODUCT INFORMATION

#### 3 MM THICKNESS

Roll Width	48" (121.92 cm)
Roll Length	100' (30.5 m)
Coverage per Roll	400 ft <sup>2</sup> (37.2 m <sup>2</sup> )
Weight per Roll	31.6 lbs (14.3 kg)
Rolls per Pallet	18

#### 6 MM THICKNESS

Roll Width	39" (99 cm)	48" (121.92 cm)	60" (152.4 cm)
Roll Length	61.5' (18.7 m)	65' (19.81 m)	50' (15.24 m)
Weight per Roll	15.8 lbs (7.17 kg)	21.84 lbs (9.91 kg)	21 lbs (9.53 kg)
Coverage per Roll	200 ft <sup>2</sup> (18.6 m <sup>2</sup> )	260 ft <sup>2</sup> (24.15 m <sup>2</sup> )	250 ft <sup>2</sup> (23.23 m <sup>2</sup> )
Rolls per Pallet	18	18	18

#### 10 MM THICKNESS

Roll Width	39" (99 cm)	48" (121.92 cm)	60" (152.4 cm)
Roll Length	40' (12.2 m)	45' (13.72 m)	45' (13.72 m)
Weight per Roll	8.9 lbs (4 kg)	12.3 lbs (5.6 kg)	15.4 lbs (7 kg)
Coverage per Roll	130 ft <sup>2</sup> (12.1 m <sup>2</sup> )	180 ft <sup>2</sup> (16.7 m <sup>2</sup> )	225 ft <sup>2</sup> (20.9 m <sup>2</sup> )
Rolls per Pallet	18	18	18

### INSTALLATION & LIMITATIONS

See technical data sheet available at [VenTek.pro](http://VenTek.pro) for limitations and complete installation instructions.



#### Maxxon Corporation

920 Hamel Road PO Box 253  
Hamel, Minnesota 55340  
800-238-8461

[ventek.pro](http://ventek.pro)  
[info@maxxon.com](mailto:info@maxxon.com)

@Maxxon.Corporation  
 maxxon-corporation